

## **BEST 4 SUBMERSIBLE ELECTRIC PUMP / DSP40 FITTING**

<https://www.securhit.com/en/dewatering-pumps/112-electropompe-submersible-best-4-raccord-dsp40.html>

Submersible electric pumps made entirely of AISI 304 stainless steel with DSP40 fitting



### **Description**

The BEST 4 submersible electric pump can be used for: lifting seepage water, emptying cellars, garages and basements, draining small and medium-sized building sites.

It is versatile, it can be used in fixed or mobile installations, it is equipped with a 10 m power cable type H07 RN-F and is available with or without float.

It is equipped with a permanent capacitor and a thermo-amperometric protection with automatic reset incorporated for the single-phase motor.

Pump body, impeller, suction grid, motor cover, seal support disc and motor casing in AISI 304, shaft in AISI 303, double mechanical seal with oil chamber: upper in Carbon/Ceramic/NBR (motor side) and lower in SiC/SiC/NBR (pump side).

Maximum immersion: 7 m for pumps with 10 m cable

Maximum liquid temperature: 35°C

Maximum solids passage: 10 mm

Maximum height (HMT): 19 m

With DSP40 fitting.

### **Caractéristiques**

- Weight : 13.8 kg

- Height : 340 mm
- Maximum flow : 22 m3/h