
PETZL ASAP MOBILE ROPE FALL ARRESTER

https://www.securhit.com/en/pulleys-and-ascenders/1259-antichute-mobile-sur-corde-petzl-asap.html

ASAP® - Compact Mobile Fall Arrester for Rope







Description

The ASAP® mobile fall arrester is a compact rope safety device designed to provide reliable fall protection for work at height. As an essential component of a fall protection system, it allows professionals to move along ropes safely while maintaining maximum mobility and protection.
During normal use, the device moves freely along the rope, both upward and downward, without requiring manual intervention. In the event of a fall or uncontrolled descent exceeding 2 m/s, the device automatically locks onto the rope to instantly stop the fall. Thanks to its robust and compact design, the ASAP® is ideal for maintenance, inspection and technical interventions at height, where reliable fall protection equipment is essential.

High-performance mobile fall arrester
- Stops falls and uncontrolled descents exceeding 2 m/s Locks automatically on the rope, even if the user grabs the device during the fall
- Works on vertical, horizontal or angled ropes
- Compatible with ropes from 10 to 13 mm in diameter
- Effective in all conditions (frozen, wet or muddy ropes) thanks to its toothed wheel

Compact and easy to use
- Quick installation and removal at any point on the rope
- Smooth movement along the rope without manual intervention
- Lightweight and compact design, ideal for professional use

Use with energy absorber
The ASAP® must be used with an energy absorber to ensure optimal fall protection:
- ASAP'SORBER 20 or ASAP'SORBER 40 for single-user applications up to 140 kg
- ASAP'SORBER AXESS for rescue operations with up to 250 kg load
The device can be used as a primary fall arrest system or as a backup safety device in rope access systems.

Technical specifications
- Rope compatibility: 10 to 13 mm

- Weight: 190 g
- Materials: aluminum, stainless steel, polyamide

Certifications:
CE EN 12841 type A, CE EN 353-2, ANSI Z359.15, GB/T 24537, XF 494 : FZL-Z-Q10/13

Caractéristiques

- Weight : 190 g
- Compatibilité corde : 10 à 13 mm