QUARTER-TURN POKET WYE DIVISION YELLOW HP 40 BAR GFR F 20 / 2 x GFR M 20 PN40 ALUMINUM

https://www.securhit.com/en/valve-fittings/1261-division-1-4-de-tour-poket-wye-jaune-hp-40bar-gfr-f-20-2-x-gfr-m-20-pn40-alu.html

PN40 POKET WYE Division - High-Pressure Aluminum Firefighting Wye



Description

The PN40 POKET WYE division is designed for firefighting applications and high-pressure water distribution systems. Robust and lightweight, it efficiently splits flow while maintaining optimal performance.

Technical specifications
- Nominal pressure: PN40
- Inlet: Female GFR DN20 PN40 (aluminum)
- Outlets: 2 x Male GFR DN20 PN40 (red anodized aluminum)
- Dimensions: 176 x 188 x 102 mm
- Weight: 1.77 kg
- Operation: 1/4 turn valve
- Material: Heat-treated aluminum alloy
- Body type: Cast
- Surface treatment: Polyester coating (corrosion-resistant)

Performance and reliability
Thanks to its full bore design, this firefighting wye minimizes pressure loss and ensures a consistent, high flow rate. The aluminum construction provides an excellent balance of strength, durability, and reduced weight.

Key benefits
- High-pressure PN40 firefighting division
- Low pressure loss for optimal flow

- Lightweight and durable aluminum construction
- Quick and easy 1/4 turn operation
- Corrosion resistance

The PN40 POKET WYE division is a reliable solution for efficient water distribution in demanding environments.

Caractéristiques

- Dimensions : 176 x 188 x 102 mm
- Weight : 1.77 kg