

YELLOW RECHARGEABLE ATEX ZONE 0 HEADLAMP XPR-5562GX

<https://www.securhit.com/en/atex-lighting/1270-lampe-frontale-jaune-xpr-5562gx-rechargeable-atex-zone-0.html>

Rechargeable ATEX Zone 0 Headlamp XPR-5562GX □ Certified Professional LED Lighting



Description

The XPR-5562GX is a Zone 0 ATEX rechargeable headlamp designed for high-risk industrial environments: petrochemical sites, gas facilities, mines, industrial maintenance, firefighting operations, and explosive atmospheres.

Certified cULus, ATEX Zone 0, and IECEx, it ensures safe use in hazardous environments.

Thanks to its ultra-low-profile design, this headlamp fits perfectly on hard hats and fire helmets with flip-up face shields, without needing to be removed when raising or lowering the visor.

High-Performance Dual LED Beam

The XPR-5562GX features two powerful LED light sources:

- High / low brightness spotlight for long-distance illumination
 - High / low brightness wide floodlight for close-range tasks
 - Dual-Light □ mode: spotlight + floodlight simultaneously for maximum visibility and enhanced safety
- Its TIR (Total Internal Reflection) lens optimizes light output and beam distribution.

Power and Runtime

- Up to 300 lumens in Dual-Light mode
- Maximum beam distance: 120 meters
- Up to 15 hours runtime depending on mode
- Integrated rechargeable Li-Ion battery included

Fast and convenient charging via the MagMate □ magnetic USB charging system, supplied with a 1.20 m charging cable.

Extreme Durability for Heavy-Duty Use

Made from ultra-resistant engineered polymer, this professional headlamp is built to withstand the toughest working conditions:

- IP67 waterproof and dustproof
- Impact resistant: survives drops up to 2 meters

- Enhanced chemical resistance
- Multi-position adjustable tilt head

Ideal for Professionals

This ATEX rechargeable headlamp is particularly recommended for:

- Industrial maintenance
- Chemical environments
- Firefighters and rescue teams
- Confined space operations

Technical Specifications

- LED technology
- Maximum output: 300 lumens
- Spotlight output: 275 lumens
- Floodlight output: 250 lumens
- Beam distance: 120 m
- Maximum runtime: 15 h
- Protection rating: IP67
- Weight: 212 g
- Dimensions: 95 x 32 x 25 mm

Box Contents

- XPR-5562GX headlamp
- Rechargeable Li-Ion battery
- Heavy-duty rubber helmet strap
- Magnetic USB charging cable

Caractéristiques

- Dimensions : 95 x 32 x 25 mm
- Weight : 212 g
- Flux lumineux max : 300 lumens