RHINOEVAC STRAP

https://www.securhit.com/en/reconnaissance/1289-sangle-rhinoevac.html

Rhinoevac® Strap - Multi-Purpose Extraction and Securing Strap





Description

The Rhinoevac® Strap is a versatile solution designed for rescue, emergency response, and operational support activities.
Compact, durable, and ready for immediate deployment, it can be used for the rapid extraction of a casualty or distressed responder, equipment transport, and the securing of devices and equipment in the field.
Thanks to its compact Velcro® retention system, the strap occupies minimal storage space while remaining instantly accessible when needed. Its design ensures quick and efficient handling, even when wearing gloves. Robust and multifunctional, the Rhinoevac® Strap is ideal for demanding environments where reliability, ease of use, and rapid deployment are essential.

Warning: This product is not Personal Protective Equipment (PPE) and must not be used for lifting people or loads.

Key Features
- Rapid casualty or responder extraction
- Equipment handling and transport
- Securing of equipment and operational devices
- Compact, space-saving design
- Easy handling while wearing gloves
- Supplied with a large carabiner
- Reflective strip for improved visibility
- Durable construction for demanding operational environments

Technical Specifications

Strap
- Length: 1.65 m
- Width: 25 mm
- Lashing Capacity (LC): 250 daN
- Compliant with the safety factor of 2 specified in NF EN 12195-2 (03/2001)
- Stitching strength: 500 daN
- Not suitable for lifting applications

Zamak Buckle
- Zamak alloy (zinc, aluminum, magnesium, and copper)
- Direct tensile strength: 250 kg

Stitching
- Reinforced box stitching
- Sewing thread: 80 tex
- Direct tensile strength: 500 kg

Velcro® Strap
- Material: Polyamide
- Width: 20 mm
- Peel strength: 2.3 N/cm
- Average shear strength: 10 N/cm²

Reflective Tape
- Metallized glass microbead technology
- Coated with an elastomeric resin for enhanced durability and visibility

Identification Label
- Blue PVC (PES) label
- Marked with the Lashing Capacity (LC) in accordance with NF EN 12195-2
- Safety marking: □Do not use for lifting□

Supplied With
- Rhinoevac® Strap
- Large model carabiner

Important: The Rhinoevac® Strap is not PPE and must never be used for lifting, fall protection, belaying, or any life-safety application.

Caractéristiques

- Charge maximale d'utilisation : 250 daN