

SERH-50V HIGH PRESSURE PETROI MOTORPUMP WITH FITTINGS AND PLUGS

<https://www.securhit.com/en/pompes-incendie/212-motopompe-serh-50v-avec-raccords-et-bouchons.html>
Motorpump with fittings and plugs



Description

The SERH-50V gasoline motor pump is a high pressure pump that can be used for first response firefighting, irrigation or liquid transfer. It is compact, lightweight and easily transportable.

It is equipped with a Honda GX160 4-stroke gasoline engine with a maximum power of 5.3 HP and a displacement of 163 cc. The 3.1L tank offers autonomy of approximately 1 hour. Starting is done by a manual cable starter.

Performance:

Maximum flow: 26 m³/h

Maximum pressure: 8 bars

Flow rate at 3 bar: 350 l/min

Flow rate at 6 bar: 225 l/min

Flow rate at 7.5 bar: 100 l/min

Maximum suction height: 8 m

Maximum grain size: 3 mm

Features

Dimensions: 555 x 450 x 468 mm

Weight: 34 kg

Suction inlet: 1 x BSP 2" equipped with a SYM40 connection and a cap (other on request)

Discharge outlets: 1 x BSP 2" □ 2 x BSP 1" of a DSP40 fitting with cap and two SYM20 fittings with caps (other on request)

Caractéristiques



- Dimensions : 55.5 x 45 x 46.8 cm
- Weight : 34 kg
- Maximum capacity : 430 L/min
- Pression maximale : 8 bar