N SECURHIT

PORTABLE FIRE PUMP WITH COUPLINGS

https://www.securhit.com/en/pompes-incendie/226-motopompe-incendie-zl1000-avec-raccords.html FIREFIGHTING PUMP ZL1000 four-cycle gasoline engine, maxi. flow 1320 liters/mn., maxi. pressure 15 Bar



Description

The ZL1000 gasoline fire pump is a single-stage centrifugal type in anodized aluminum alloy resistant to seawater with stainless steel shaft and mechanical seal. High performance, it can deliver more than 1000 l/min at 8 bar. The ZL1000 gasoline fire pump is made in Germany, a guarantee of excellent quality. It is particularly suitable for firefighters and fire safety services for supplying fire hoses or monitor nozzles. It can also be loaded into emergency vehicles, on trailers, on boats, etc.

PUMP Type: Single stage centrifugal Material: Anodized aluminum 1 x Suction (4 ½") with filter grid equipped with half AR100 connection or other on request 2 x Discharge (2 ½") with handwheel valves equipped with DSP65 half connections or other on request

PERFORMANCE Nominal flow 750 l/min at 10 bar and 3 m suction height Max flow 1320 l/min Max pressure 15 bar Flow rate at 6 bar and 3m suction height: 1180 l/min Flow rate at 8 bar and 3m suction height: 1000 l/min Flow rate at 10 bar and 3m suction height: 800 l/min Flow rate at 12 bar and 3m suction height: 550 l/min

PRIMING

VACUMAT automatic priming pump Max suction height 8m Oil-free, maintenance-free, pressure-free

N SECURHIT

EQUIPMENT

Tubular protection frame with 4 retractable handles (rubber coated), suction and discharge pressure gauges, hour meter, drain valve, external charger, integrated spotlight

ENGINE Briggs & Stratton gasoline engine (2 cylinders, 4 stroke) Air-cooled, electric start with battery Tank capacity 14 liters

FEATURES Dimensions: 910 x 597 x 755 mm Weight with aluminum pump: 135 kg dry (145 kg fully loaded)

Caractéristiques

- Dimensions : 965 x 775 x 692 mm
- Weight : 143 kg
- Efficiency : 750 l/min à 10 bar
- Pression maxi : 15 bar
- Débit maxi : 1320 l/min