

ISORAFT LIFE RAFT

<https://www.securhit.com/en/radeau-de-survie/253-radeau-de-survie-isoraft-10-personnes.html> Liferaft designed to withstand rough sea



Description

Isoraft rafts are designed to withstand the assaults of rough seas and are extremely reliable. Automatic inflation of the 2 independent chambers by a 12 meter line with a sufficiently large gas reserve. Thermally insulated floor, ventilation, rainwater collection gutter. Internal stabilization and righting system adapted to the handling by one person.

Standard equipment: 1 bailer, 2 sponges, 1 pair of paddles, 1 whistle, 1 flashlight, 1 signal mirror, anti-seasickness pills, vomit bag (one per person), hand-held red light, parachute flares, repair kit, 1 manual bellows, 1 life-saving signal board, 1 logbook, 1 mooring line, 1 knife, 1 floating anchor and a 30-meter line.

Isoraft liferafts are manufactured and tested according to ISO 9650-1 and 9650-3 standards, for recreational boating (each liferaft must be checked at least within 2 years of installation or before 3 years from the date of manufacture).

The Isoraft liferaft is available for 6 persons (1200 x 2104 x 2104 mm), 8 persons (1250 x 2390 x 2390 mm), 10 persons (1400 x 2694 x 2694 mm) and 12 persons (1500 x 2924 x 2924 mm).

It can be stored in containers or in waterproof bags.

Caractéristiques

- Operating temperature : De -15° à +65°C
- Maximum securing height : 36m au dessus du niveau de la mer