

HYDRA 2 FLOATING PUMP WITH DSP 65 FITTING

<https://www.securhit.com/en/pompes-incendie/302-flotopompe-hydra-2-avec-raccord-dsp-65.html> Portable fire float pump



Description

The Hydra 2 float pump has a maximum flow rate of 1180 l/min and a maximum pressure of 4.5 bars, making it one of the highest-performing floating water pumps in its category. It is ideal for pumping water from natural sources. It also serves as an effective aid for firefighters during operations where water pumping is necessary, or for filling tanks, draining flooded areas, or extinguishing fires.

The pump is made of aluminum alloy, and the float is made of highly resistant rotomolded polyethylene.

It is equipped with a 4-stroke Briggs and Stratton engine of 6.5 HP and has 4 large carrying handles, making it very ergonomic.

The floating water pump comes with a DSP 65 connection and can also be supplied with a simple threading or other types of connections upon request.

DESCRIPTION

- New construction for improved performance.
- Integrated fuel tank with a volume of 6L.
- Operating time of over 3 hours. New ergonomic design.
- Easy handling thanks to 4 handles.
- Compact shape and dimensions.
- Ergonomic float for better stability.

FEATURES

- Max flow rate: 1180 l/min
- Max head: 45 meters
- Starting system: Manual
- Weight: 29 Kg empty / 34 kg full
- Dimensions: 786 x 595 x 392 mm
- Flow at 0.5 bar: 1075 l/min

Flow at 1 bar: 1014 l/min

Flow at 3 bar: 380 l/min

Flow at 4 bar: 150 l/min

Caractéristiques

- Dimensions : 786 x 595 x 392 mm
- Autonomy : 3 heures
- tare weight : 29 kg
- tank volume : 6 litres
- Fully loaded weight : 34 kg