

PS TRICO SEMI-RIGID HOSE

https://www.securhit.com/en/fire-hoses-and-accessories/367-134-tuyau-semi-rigide-ps-trico.html#/131-diametres_sp25dt-dn_25/132-longueurs_sp25dt-_20_m/133-raccords_sp25dt-_raccord_mf_gfr_bronze

Firefighting Semi-rigid PVC hose for PS axial feeder



Description

Semi-rigid hose for fire fighting vehicles equipment of the first aid type

Designed in thermoplastic material with polyester fiber textile reinforcement. Compliant with the NF EN 1947:2014 standard type A class 2.

Light and flexible, the T1947 hoses easily withstand shocks and crushing. They are well-suited for winding on the reels of vehicles without flattening.

Their coating is resistant to ultraviolet rays and abrasion, giving them excellent aging resistance.

Applications

Firefighting
Rescue services

Connections

Firefighting connection type GFR, symmetric or Storz with crimped collar.

Characteristics

Weight per meter: 466 gr
Inner diameter: 25.5 mm
Outer diameter: 33.33 mm
Thickness: 3.9 mm
Working pressure: 16 bars

Burst pressure: 45 bars
Bending radius: 440 mm

Caractéristiques

- Certification : NF EN 1947
- Poids au mètre : 466 gr