

HIGH CAPACITY TANK WITH COLLAPSIBLE STRUCTURE

https://www.securhit.com/en/citernes-et-reservoirs/383-193-reservoir-temporaire-ouvert-avec-armature-metallique.html#/187-modeles_ettank-20000_ The ECCOTARP collapsible spill bunds are versatile protective equipment made of chemically resistant material.



Type du réservoir	ETTANK 5000	ETTANK 7500	ETTANK 20000	ETTANK 35000	ETTANK 50000
Volume (l)	5000	7500	20000	35000	50000
Diamètre (mm)	2300	2700	4200	5500	6600
Hauteur (mm)	1300	1300	1500	1500	1500
Nombre montants/soutiens	6/2	6/2	10/4	12/4	12/4
Dimensions de l'emballage (mm) et poids de la structure métallique (kg)	300 x 200 x 1350 30	300 x 200 x 1600 30	500 x 300 x 1550 50	500 x 300 x 1550 60	500 x 300 x 1700 70
Dimensions de l'emballage (mm) et poids du film plastique (kg)	300 x 200 x 800 20	300 x 200 x 800 25	400 x 400 x 1000 50	600 x 400 x 1100 70	800 x 500 x 1200 90

Description

The ECCOTARP collapsible spill bunds are versatile protective equipment made of chemically resistant material (PVC reinforced fabric). They are portable, lightweight and easily shapeable. That is why they are effective especially in fast deployment during accidents. Their advantage is their adaptability to various obstacles and uneven surfaces. Due to their resistance to chemicals and petroleum products they can be used in a wide range of applications, especially in emergency services, petrochemical industry, logistic and industrial warehouses, lorry transport and shipping, during elimination of machinery defects on shop floors, at the airports and in the ports, in agriculture and forestry, i.e. everywhere where hazardous substances might leak.

The tank is suitable, for example, for helicopter firefighting using the bambi bucket or for repumping materials at places difficult to reach.

The tank is made of a highly resistant PES/PVC material providing the temperature range of use of -30 °C to +70 °C. The material is resistant against chemical and oil substances there by providing enhanced potential of use in environmental accidents. The tank can be filled very quickly using the filling elbow with C52 (B75/other) end piece in the upper part of the structure. A fill/discharge valve (type according to customer's choice) is located in the bottom part of the tank. The maximum slope of the tank is 8%.