NEON YELLOW FLAMMENFLEX ULTRA HOSE

https://www.securhit.com/en/fire-hoses-and-accessories/384-198-tuyau-flammenflex-jaune-fluo.html#/192-diametres_ffgjf-dn110/193-longueurs_ffgjf-10_m/194-raccords_ffgjf-ar_100

Robust and flexible fire hose



Description

The Flammenflex Ultra fire hose is a premium quality textile hose. It is lightweight and flexible for use with excellent abrasion resistance. It is used by Firefighters for firefighting and is suitable for combating forest fires as well as for interventions in urban or industrial environments.

The Flammenflex Ultra hose offers excellent visibility with its fluorescent yellow color. Light, flexible, and pliable, it is resistant to abrasion, many chemicals, and seawater. Its design results in only low pressure drop. The Flammenflex Ultra hose withstands cold temperatures up to -30°C and heat up to +100°C.

The Flammenflex Ultra hose complies with NFS 61112, DIN 14811, PREN1924-1, EN14540 standards.

It requires no special maintenance and can be repaired by hot vulcanization. It can be supplied on request with customized marking or leak-proof sleeves.

Technical Specifications:

Manufacture: Textile cover and bonded rubber inner tube
Thickness: 1.7 mm
Construction: High-strength polyester jacket, reinforced circular weaving
Inner layer: Double EPDM rubber coating (superior quality)
Color/signage: Fluorescent yellow striped blue-red-blue

The range for Firefighters is available in 4 diameters and 2 lengths equipped with half-couplings:

FLAMMENFLEX ULTRA DN25
Weight per meter: 130 gr

Maximum working pressure: 40 bars
Burst pressure: 90 bars
Available in 20 and 40m
Equipped with crimped half-couplings GFR 20, SYM 20, or others by choice

FLAMMENFLEX ULTRA DN45
Weight per meter: 220 gr
Maximum working pressure: 16 bars
Burst pressure: 60 bars
Available in 20 and 40m
Equipped with crimped half-couplings DSP 40 or others by choice

FLAMMENFLEX ULTRA DN70
Weight per meter: 380 gr
Maximum working pressure: 16 bars
Burst pressure: 60 bars
Available in 20 and 40m
Equipped with crimped half-couplings DSP 65 or others by choice

FLAMMENFLEX ULTRA DN110
Weight per meter: 650 gr
Maximum working pressure: 12 bars
Burst pressure: 35 bars
Available in 10, 20, and 40m
Equipped with crimped half-couplings AR 100 or others by choice

Caractéristiques

- Coloris : Jaune fluo