

INTRAX FLUORESCENT YELLOW HOSE

https://www.securhit.com/en/fire-hoses-and-accessories/385-207-tuyau-intrax-jaune-fluo.html#/205-diametres_intjf-dn_45/206-longueurs_intjf-20_m/207-raccords_intjf-dsp_40

INTRAX fire hose



Description

Thanks to its exclusive multi-layer embossed weaving process, the Intrax hose offers an unprecedented compromise between high burst pressure 90 bar, low curvature radius 190mm, abrasion resistance and lightness. It is supplied in fluorescent color with black edging for better visibility.

FEATURES

- Double 3D interwoven polyester cover, reinforced circular weave
- External embossed coating (rough feel) for high resistance to abrasion (exclusive patented process)
- Double interior coating of EPDM rubber
- High burst and working pressure
- Very high flexibility, including under pressure
- Very small radius of curvature (avoids the formation of creases sensitive to floor abrasion)
- Its exclusive design allows it to maintain the lightness specific to flexible canvas hoses without coating.
- Possibility of storage without drying
- Resists many chemicals and sea water
- High visibility contrasting neon and black colors
- Possibility of anti-leak sleeves on request
- Possibility of personalized marking on request
- Austrian design and manufacturing

The Intrax fire hose is only available in diameter 45 in lengths of 20 or 40m equipped with crimped aluminum DSP40 fittings
Operating pressure: 30 bar
Non-bursting pressure: 90 bar

Weight per m: 290 gr

Bending radius: 190 mm

Weight of a 20m ring equipped with DSP40 half-couplings: 6.1 kg

Caractéristiques

- Pression d'éclatement : 90 bar
- Rayon de courbure : 190 mm