INTRAX FLUORESCENT YELLOW HOSE

https://www.securhit.com/en/fire-hoses-and-accessories/385-207-tuyau-intrax-jaune-fluo.html#/205-diametres_intjf-dn_45/206-longueurs_intjf-20_m/207-raccords_intjf-dsp_40

Intrax Fire Hose - High Performance, Lightweight, and High Visibility





Description

The Intrax fire hose stands out thanks to its exclusive multi-layer embossed weaving process, offering a unique combination of high burst pressure, flexibility, and abrasion resistance.
Designed for demanding professionals, it delivers safety, maneuverability, and long-lasting performance, while remaining lightweight and easy to handle.
Its fluorescent color with black stripe ensures maximum visibility in operational conditions.

Technical Features
- 3D multilayer weaving: double interlaced polyester jacket with reinforced circular weave for optimal durability.
- Embossed outer coating: textured surface for excellent abrasion resistance, exclusive patented process.
- Double EPDM inner lining: ensures perfect sealing and enhanced longevity.
- High pressure: service pressure 30 bar, burst pressure 90 bar.
- Exceptional flexibility: very small bending radius (190 mm) to prevent abrasion-prone kinks.
- Lightweight design: retains the maneuverability of uncoated fabric hoses.
- Easy storage: can be stored without drying.
- Resistant to chemicals and seawater.
- Customizable options: anti-leak couplings and personalized markings available on request.
- Austrian-made: guaranteeing quality and reliability.

Availability and Dimensions
- Diameter: 45 mm
- Lengths: 20 m or 40 m
- Weight per meter: 290 g

- Weight of a 20 m coil with half DSP40 couplings: 6.1 kg
- Equipped with DSP40 aluminum crimped couplings

The Intrax fire hose is ideal for demanding operations where pressure, durability, flexibility, and visibility are critical. Its exclusive design and premium materials make it a reliable tool for firefighters and professional fire safety teams.

Caractéristiques

- Pression d'éclatement : 90 bar
- Rayon de courbure : 190 mm