XPR-5592 RECHARGEABLE ATEX PROJECTOR

https://www.securhit.com/en/atex-lighting/400-231-projecteur-atex-rechargeable-xpr-5592.html#/242-modeles_xpr_5592-gcx_kit_complet

ATEX LED Floodlight XPR-5592GX / GCX Zone 0 - 1200 Lumens Rechargeable





Description

The XPR-5592GX Rechargeable LED Scene Light is ideal for use when portability is important. cULus, ATEX, INMETRO, and IECEx-certified Intrinsically safe for use in hazardous environments, the array of 5 floodlight LEDs perfectly emit an impressive 1,200 lumens on high for 6 hours, or 650 lumens on low for 12 hours when activated using the robust three-position toggle switch. The housing is constructed from lightweight glass-filled nylon polymer, keeping it cool to the touch while being chemical, heat, and impact resistant.

A heavy-duty rare-earth magnetic base is securely mounted on the bottom to provide 360 degrees of hands-free rotation for proper light placement on any job site. Powered by an integrated lithium-ion battery, the light includes an adjustable steel handle for carrying or hanging and both AC/DC power supplies placed inside a durable blow-molded carrying case for ease of use and storage.

CERTIFICATIONS
ATEX zone 0, IECEx, InMetro, CE, BC, cULus, UKCA
Meets requirements of NFPA 1971-8.6 (2013)

CASE MATERIAL
Glass-filled nylon polymer
Serialized for personal identification

LUMENS/RUNTIME
HIGH: 1200 Lumens, 6 hrs. runtime
LOW: 650 Lumens, 12 hrs. runtime

WATER RATING
IP-67 (dust-proof, waterproof)

DROP RATING
2 meters

DIMENSIONS
LENGTH: 343 mm
WIDTH: 235 mm
DEPTH: 89 mm
WEIGHT: 1928 gr

BATTERY
Integrated rechargeable li-ion battery

WARRANTY
1 Year limited warranty

WHAT□S INCLUDED
XPR-5592GX
- Scene Light
- AC & DC charging cords
- Blow-molded case

XPR-5592GCX
- Scene Light
- 6 foot tripod
- AC & DC charging cords
- Blow-molded case

Caractéristiques

- Dimensions : 343 x 235 x 89 mm
- Weight : 1928 g