

## XPR-5592 RECHARGEABLE ATEX PROJECTOR

[https://www.securhit.com/en/eclairage-atex/400-231-projecteur-atex-rechargeable-xpr-5592.html#/242-modeles\\_xpr\\_5592-gcx\\_kit\\_complet](https://www.securhit.com/en/eclairage-atex/400-231-projecteur-atex-rechargeable-xpr-5592.html#/242-modeles_xpr_5592-gcx_kit_complet) Atex zone 0 rechargeable floodlight



### Description

The XPR-5592GX Rechargeable LED Scene Light is ideal for use when portability is important. cULus, ATEX, INMETRO, and IECEx-certified Intrinsically safe for use in hazardous environments, the array of 5 floodlight LEDs perfectly emit an impressive 1,200 lumens on high for 6 hours, or 650 lumens on low for 12 hours when activated using the robust three-position toggle switch. The housing is constructed from lightweight glass-filled nylon polymer, keeping it cool to the touch while being chemical, heat, and impact resistant.

A heavy-duty rare-earth magnetic base is securely mounted on the bottom to provide 360 degrees of hands-free rotation for proper light placement on any job site. Powered by an integrated lithium-ion battery, the light includes an adjustable steel handle for carrying or hanging and both AC/DC power supplies placed inside a durable blow-molded carrying case for ease of use and storage.

#### CERTIFICATIONS

ATEX zone 0, IECEx, InMetro, CE, BC, cULus, UKCA  
Meets requirements of NFPA 1971-8.6 (2013)

#### CASE MATERIAL

Glass-filled nylon polymer  
Serialized for personal identification

#### LUMENS/RUNTIME

HIGH: 1200 Lumens, 6 hrs. runtime  
LOW: 650 Lumens, 12 hrs. runtime

#### WATER RATING

IP-67 (dust-proof, waterproof)

#### DROP RATING

2 meters

#### DIMENSIONS

LENGTH: 343 mm

WIDTH: 235 mm

DEPTH: 89 mm

WEIGHT: 1928 gr

#### BATTERY

Integrated rechargeable li-ion battery

#### WARRANTY

1 Year limited warranty

#### WHAT'S INCLUDED

XPR-5592GX

- Scene Light
- AC & DC charging cords
- Blow-molded case

XPR-5592GCX

- Scene Light
- 6 foot tripod
- AC & DC charging cords
- Blow-molded case