

INTRANT XPR-5568RX ATEX ZONE 0 TORCH WITH 12-220V CHARGER

<https://www.securhit.com/en/atex-lighting/402-torche-atex-xpr-5568rx-chargeur-12-220v.html>

Atex zone 0 angled torch with combined lighting



Description

The INTRANT XPR-5568RX Intrinsically Safe rechargeable angle light is a flashlight, a floodlight, and a Dual-Light angle light that is ATEX Zone 0 certified Intrinsically Safe.

The flashlight rotates 90 degrees up and down with a 45 degree downward angled floodlight. The flashlight setting offers user-selectable brightness settings of 200, 110, and 60 lumens with a 401 meter beam distance. The ultra-tight beam is perfect for cutting through smoke and lighting up objects at great distances. The floodlight setting has user-selectable brightness settings of 100, 40, and a Survival Mode of 20 lumens that provides just enough light in an emergency situation with a run-time of 27 hours. The Dual-Light mode allows the user to simultaneously see objects at a distance or through the smoke, as well as see the ground in front of them as they walk or work.

Powered by a single Li-ion battery pack and includes a AA battery carrier to provide backup power if needed. Rated IP-67 dustproof/waterproof. Meets the requirements of NFPA-1971-8.6 (2013).

CASE MATERIAL

- Engineered polymer

LUMENS/RUNTIME

FLASHLIGHT

- HIGH: 200 Lumens, 7 hrs. runtime
- MEDIUM: 110 Lumens, 15 hrs. runtime
- LOW: 60 Lumens, 27 hrs. runtime
- STROBE

FLOODLIGHT

- HIGH: 100 Lumens, 7 hrs. runtime

- MEDIUM: 40 Lumens, 15 hrs. runtime
- SURVIVAL: 20 Lumens, 27 hrs. Runtime

DUAL-LIGHT

- 205 Lumens, 7 hrs. runtime

BEAM DISTANCE

FLASHLIGHT

- HIGH: 401m
- MEDIUM: 250m
- LOW: 187m

WATER RATING

- IP-67 (dustproof and waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 168mm
- WIDTH: 66mm
- DEPTH: 66mm
- HEAD DIAMETER: 53mm
- WEIGHT: 301gr (with batteries)

BATTERY

- Rechargeable Li-ion battery pack
- AA Battery carrier (batteries not included)

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Angle light
- Rechargeable Li-ion battery pack
- AA battery carrier
- Snap-in rapid charger (Charge Input: 24VDC max) Meets requirements of NFPA
- AC & DC power supplies
- Instruction manual

Caractéristiques

- Dimensions : 168 x 66 x 66 mm Ø 53 mm
- Weight : 301 g (avec batterie)
- Certification : Atex zone 0