

## INTEGRITAS XPR-5582RX rechargeable lantern / 12-220V CHARGER

<https://www.securhit.com/en/handheld-lighting/404-projecteur-antideflagrante-xpr-5582rx-integras-chargeur-12-220v.html>

Ultra-bright floodlight with articulated head



### Description

This light generates an ultra-bright 1750 lumens from four separate LEDs housed in a 180-degree articulating head. The results are a tightly collimated beam that cuts through thick smoke and illuminates objects up to a third of a mile (552m) away. Holding down the switch enables a battery-saving 600-lumen low mode, extending runtime to 11.5 hours when firefighters need bright, useful light for longer calls. Designed and engineered as both a hand-held lantern and portable area light, the 5582 features a rear-mounted rubber base pad for upright use on any flat surface, providing instant, adjustable scene lighting on demand.

Constructed of thick-walled glass-filled nylon and weighing only 2 lbs. 11oz. The wide, flat body and handle design provide firefighters a stable platform while crawling under smoke or following a hose line. Two bright green rear-facing LEDs provide passive team member locations for increased safety and awareness. Certified cETLus-certified Class I DIV 2 and meets the requirements of NFPA-1971-8.6 (2013). Powered by an integrated rechargeable li-ion battery. Includes a charger base, AC charger, direct-wire DC charger cable with an in-line fuse as well as a carry strap.

Features:

- ☐ Adjustable tilting head
- ☐ 1,750 Lumens for 5 hours
- ☐ Rear green LED lights
- ☐ Low battery indicator
- ☐ Locking snap-in charger
- ☐ Removable shoulder strap
- ☐ Integrated rechargeable lithium-ion battery

Approval Lab Product Rating:

- ☐ CLASS I DIV 2: GRPS A-D T3

- CLASS II & III DIV 2: GRPS F-G T135°C
- CLASS I ZONE 2: GROUP IIC T3

## Caractéristiques

- Dimensions : 19.2 x 10.8 x 14.8 cm
- Weight : 1 219 g
- Waterproofing : IP-67