

## VF2000D DIESEL FIRE PUMP

[https://www.securhit.com/en/fire-pump/424-358-motopompe-incendie-diesel-vf2000d.html#/357-corps\\_pompe\\_vf2000d-aluminium](https://www.securhit.com/en/fire-pump/424-358-motopompe-incendie-diesel-vf2000d.html#/357-corps_pompe_vf2000d-aluminium)

Portable Diesel fire pump



### Description

Single-stage centrifugal fire pump in anodized aluminum alloy resistant to seawater (bronze pump optional), stainless steel shaft, mechanical seal.

1 x Suction (4 ½") with filter screen equipped with a half coupling AR100 or others on request  
2 x Discharge (2 ½") with handwheel valves equipped with half couplings DSP65 or others on request

#### PERFORMANCE

Nominal flow rate 2000 l/min at 8 bar and 3 m suction height  
Max. flow rate 2450 l/min  
Max. pressure 12.5 bar

#### PRIMING

Automatic priming pump VACUMAT  
Max. suction height 8 m  
Oil-free, maintenance-free, pressure-free

#### EQUIPMENT

Tubular protection frame with 4 retractable handles (rubber-coated), suction and discharge pressure gauges, hour meter, spotlight, 4 lifting rings, drain valve, external charger.  
Galvanized steel skid chassis available on request

#### ENGINE

DEUTZ diesel engine (Euro 2, 4 cylinders, 4 stroke)

Air cooling, electric start with battery  
Fuel tank capacity 30 Liters (60 liters optional)

## SPECIFICATIONS

Dimensions 1615 x 785 x 858 mm

Weight with aluminum pump: 410...440 kg dry (445...475 kg with all fluids)

## Caractéristiques

- Dimensions : 1615 x 785 x 858 mm
- Engine : Diesel Deutz
- Performance : 2000 L/min à 8 bar