

## PETZL NEWTON INT HARNESS

[https://www.securhit.com/en/harnesses-and-belts/527-612-harnais-petzl-newton-int.html#/574-taille\\_c073ba-taille\\_1](https://www.securhit.com/en/harnesses-and-belts/527-612-harnais-petzl-newton-int.html#/574-taille_c073ba-taille_1)

Easy-to-install international fall arrest harness with color-coded straps. A versatile, ergonomic and lightweight device for successful work at height.



### Description

Versatile, lightweight personal protective equipment for safe work at height? PETZL's NEWTON harness, in its international version, accompanies professionals in perilous interventions.

Ergonomic design:

- A body-hugging harness with excellent freedom of movement
- Highly resistant textile sternal attachment point
- LIFT retractor connection for successful vertical descent
- Strong, durable metal dorsal attachment point (anodized aluminum)

Easy fitting:

- Color-coded straps to identify the upper and lower parts of the harness before putting it on.
- Easy opening and closing of the harness thanks to the FAST LT PLUS sternal buckle and release system to prevent accidental opening
- DOUBLEBACK self-locking buckles for quick adjustment of shoulder and thigh straps
- Optimized tool access with TOOLBAG tool holders and pouch loops

The international version of the NEWTON harness features a fall indicator. After a fall, a red strap appears, indicating the need to change harness.

Waist circumference: 70-93 cm (size 1), 83-120 cm (size 2)

Thigh circumference: 47-62 cm (size 1), 50-65 cm (size 2)

Stature: 165-185 cm (size 1), 175-200 cm (size 2)

Weight: 1125 g (size 1), 1155 g (size 2)

3-year warranty

## **Caractéristiques**

- Materials : polyamide, polyester, aluminium, acier
- Certifications : CE EN 361, EAC, ANSI Z359.11, CSA Z259.10, UKCA, JSFAD, GB 6095-2021: Z, XF 494-2004: FZL-DD-III