

## PETZL I'D EVAC DESCENDER

[https://www.securhit.com/en/belay-and-descenders/549-671-descendeur-petzl-i-d-evac.html#/625-couleur\\_d020ca-jaune](https://www.securhit.com/en/belay-and-descenders/549-671-descendeur-petzl-i-d-evac.html#/625-couleur_d020ca-jaune)

Self-braking PETZL I'D EVAC descender with anti-panic function, designed for anchored evacuations. AUTO-LOCK system to automatically lock the rope and error-indicating trigger.



### Description

Safety is essential in high-risk situations. Evacuation systems are an essential part of any rescue operation. PETZL's I'D EVAC descender is specially designed for anchored evacuations.

Easy-to-use equipment:

- A locking pawl on the mobile flange for rapid rope installation without losing the descender.
- A guide and markings for easy rope placement
- An error-indicating trigger to avoid potential accidents if the rope is incorrectly set
- Ergonomic handle for perfectly controlled descent
- Descent on the flange or in the V-shaped braking groove
- AUTO-LOCK system automatically locks the rope, without having to manipulate the handle or make a stop key
- Efficient storage of the handle once the rope has been removed from the descender

Great versatility:

- Rope cleaning in case of blockage, without having to manipulate the handle
- Pivoting cam for easy rope slack take-up and reversibility of the hauling system
- A locking screw for the mobile flange (for better integration of the descender in a rescue kit)
- Compatible with rope diameters from 10 to 11.5 mm
- Possibility of adding an additional brake for controlled descent
- Reinforced protection on the rope's friction zone to ensure greater durability

Particularly well-suited for anchored descents.

For heavy loads up to 250 kg.  
Yellow or black color.  
Weight: 615 g

## **Caractéristiques**

- Materials : Aluminium, acier, polyamide
- Charge maximale pour une personne : Jusqu'à 150 kg
- Charge maximale pour deux personnes (secours) : jusqu'à 250 kg