

ROTATING-SWINGING HOSE REELS

https://www.securhit.com/en/fire-extinguishing/554-682-ria-tournant-pivotant.html#/636-modele_ria-dn19_30_m

Fire hose reel with fire hose and diffuser



Description

The rotating-swinging hose reels DN19 and DN25 for wall installation offer the possibility to swivel easily up to 180°.

The fire hose reels are fitted with 20 or 30 metres of semi-rigid hoses.

They are fitted with a 1/4-turn valve or a handwheel valve for quick opening and closing.

Fitted with a male 3/4" BSP, 1" BSP or 1"1/2 BSP threaded, depending on the model.

European diffuser outlet: successively in closed, diffused jet and straight jet position, with anti-shock head sheath.

Conform to European standard EN 671-1.

Technical features:

DN25 - 30 m: 648 x 346 x 856 mm - 32 kg

DN25 - 20 m: 648 x 346 x 856 mm - 27 kg

DN19 - 30 m : 613 x 245 x 787 mm - 26 kg

DN19 - 20 m : 613 x 245 x 787 mm - 22 kg

DN33 - 30 m : 690 x 350 x 788 mm - 43 kg

DN33 - 20 m : 690 x 350 x 788 mm - 37 kg

Caractéristiques

- Matières : : Acier, alliage cuivreux et composites
- Pression maximale de service DN19 et DN25 : 12 bar
- Pression maximale de service DN33 : 7 bar