

PETZL COLLINOX ANCHORS - PER 10

<https://www.securhit.com/en/anchors-and-tie-back-systems/587-amarrage-pack-de-10-broches-collinox-10-mm.html>

PETZL COLLINOX bonding anchors, forged stainless steel (pack of 10). Indispensable equipment for setting up a reliable anchor point on concrete or rocks.



Description

PETZL COLLINOX glue-on anchors can be used to create reliable anchor points on various concrete or rock supports.

- Once the crumbling part of the support has been cleaned, drill a hole of the right diameter and depth.
- Clean the hole with a brush and blowgun.
- Use glass bulb glue or mixing glue gun.
- Push the anchor all the way in to the shoulder, turning it at least 10 times to ensure proper mixing (glue should be visible).
- Take into account the drying time of the glue used before loading.
- Check that the glue overflow around the mooring is hard and that the mooring does not rotate.

Material: forged stainless steel (durable and corrosion-resistant)

Dimensions: 10 x 70 mm

Weight: 95 grams

Drying time: 40 minutes to 10 hours

Pre-testing recommended on :

- Granite rock, gneiss above 80 MPa
- Hard limestone over 80 MPa
- Medium-grained limestone and sandstone 80 MPa to 45 MPa
- Soft rock below 45 MPa

- High-quality concrete above 50 MPa
- Medium-quality concrete 25 MPa to 50 MPa

Caractéristiques

- Material : acier inoxydable forgé
- Certification : EN 959