

PETZL BAT'INOX MOORINGS - PER 10

<https://www.securhit.com/en/anchors-and-tie-back-systems/589-amarrage-pack-de-10-broches-bat-inox-14-mm.html>

PETZL BAT'INOX bonding anchors, forged stainless steel (pack of 10). These are the ideal devices for installing a secure anchor point on concrete or rocks.



Description

PETZL's BAT'INOX bonding anchors are ideal for creating secure anchor points. They can be installed on various concrete or rock supports. For use with G103AA00 glue.

- After cleaning the friable part of the support, drill a hole of the right diameter and depth.
- Clean the hole with a brush and blowgun.
- Use glass-bulb glue or a mixing glue gun.
- Insert the anchor up to the shoulder, turning it at least 10 times to create a mixture (glue should be visible).
- Take into account the drying time of the glue used before loading.
- Check the hardness of the glue overflow around the mooring and that the mooring does not rotate.

Material: forged stainless steel (durable and corrosion-resistant)

Dimensions: 10 x 70 mm

Weight: 95 grams

Drying time: 40 minutes to 10 hours

Pre-testing recommended on :

- Granite rock, gneiss above 80 MPa
- Hard limestone over 80 MPa
- Medium-grained limestone and sandstone 80 MPa to 45 MPa
- Soft rock below 45 MPa

- High-quality concrete above 50 MPa
- Medium-quality concrete 25 MPa to 50 MPa

Caractéristiques

- Material : acier inoxydable forgé
- Certification : EN 959