# PETZL BAT'INOX MOORINGS - PER 10

*https://www.securhit.com/en/anchors-and-tie-back-systems/589-amarrage-pack-de-10-broches-bat-inox-14-mm.html*

PETZL BAT'INOX bonding anchors, forged stainless steel (pack of 10). These are the ideal devices for installing a secure anchor point on concrete or rocks.



## Description

PETZL's BAT'INOX bonding anchors are ideal for creating secure anchor points. They can be installed on various concrete or rock supports. For use with G103AA00 glue.

- After cleaning the friable part of the support, drill a hole of the right diameter and depth.
- Clean the hole with a brush and blowgun.
- Use glass-bulb glue or a mixing glue gun.
- Insert the anchor up to the shoulder, turning it at least 10 times to create a mixture (glue should be visible).
- Take into account the drying time of the glue used before loading.
- Check the hardness of the glue overflow around the mooring and that the mooring does not rotate.

Material: forged stainless steel (durable and corrosion-resistant)
Dimensions: 10 x 70 mm
Weight: 95 grams
Drying time: 40 minutes to 10 hours

Pre-testing recommended on :

- Granite rock, gneiss above 80 MPa
- Hard limestone over 80 MPa
- Medium-grained limestone and sandstone 80 MPa to 45 MPa
- Soft rock below 45 MPa

- High-quality concrete above 50 MPa
- Medium-quality concrete 25 MPa to 50 MPa

## Caractéristiques

- Material : acier inoxydable forgé
- Certification : EN 959