

PETZL TWIN RELEASE PULLEY

<https://www.securhit.com/en/pulleys-and-ascenders/611-poulie-bloqueur-twin-release.html>

PETZL TWIN RELEASE double release pulley for setting up 4:1 hauling systems. Ideal for work in small spaces and technical rescues.



Description

For work in confined spaces and technical rescues, it's vital to be equipped with specific devices. PETZL's TWIN RELEASE blocking pulley combines several advantages for successful missions.

- A pinless cam, lockable in the open position and disengageable using the ergonomic handle
- Excellent control when lowering heavy loads, thanks to the brake integrated into the main mobile flange
- High efficiency for 4:1 reeving systems with large-diameter, ball-bearing sheaves mounted in parallel
- A faceted main sheave with a single direction of rotation (optimum hoisting performance and fewer areas of friction with the rope)
- Simple triple-action opening of movable flanges
- Red indicator lights when flanges are unlocked
- Rope can be installed without removing the anchoring device
- A hole in the handle for a remote control cord
- A swivel to guide the pulley under load, with an additional attachment point for easier manoeuvring (accommodating a maximum of three carabiners).

Rope diameter: between 8 and 13 mm.

Faceted sheave diameter: 40 mm.

Sheave diameter: 38 mm.

Yield: 95%.

Maximum working load: 280 kg.

Auxiliary attachment point breaking load: 22 kN.

Breaking load: 36 kN.

Caractéristiques

- Weight : 800 g
- Materials : Aluminium, acier inoxydable, polyamide
- Certifications : CE EN 567, CE EN 12278 partielle*, NFPA 2500 Pulley General Use, NFPA 2500 Rope Grab Technical Use, UKCA, XF 494: FZL-H-T 9.5/13, XF 494: FZL-Z-Q 9.5/13 * Passe les exigences de performances de la norme CE EN 12278
- Certification du système : ANSI Z359.4 Synthetic Rope Tackle Block (plus d'informations dans la notice technique)