# PETZL TWIN RELEASE PULLEY

*https://www.securhit.com/en/pulleys-and-ascenders/611-poulie-bloqueur-twin-release.html*

PETZL TWIN RELEASE double release pulley for setting up 4:1 hauling systems. Ideal for work in small spaces and technical rescues.









## Description

For work in confined spaces and technical rescues, it's vital to be equipped with specific devices. PETZL's TWIN RELEASE blocking pulley combines several advantages for successful missions.

- A pinless cam, lockable in the open position and disengageable using the ergonomic handle
- Excellent control when lowering heavy loads, thanks to the brake integrated into the main mobile flange
- High efficiency for 4:1 reeving systems with large-diameter, ball-bearing sheaves mounted in parallel
- A faceted main sheave with a single direction of rotation (optimum hoisting performance and fewer areas of friction with the rope)
- Simple triple-action opening of movable flanges
- Red indicator lights when flanges are unlocked
- Rope can be installed without removing the anchoring device
- A hole in the handle for a remote control cord
- A swivel to guide the pulley under load, with an additional attachment point for easier manoeuvring (accommodating a maximum of three carabiners).

Rope diameter: between 8 and 13 mm.
Faceted sheave diameter: 40 mm.
Sheave diameter: 38 mm.
Yield: 95%.
Maximum working load: 280 kg.
Auxiliary attachment point breaking load: 22 kN.
Breaking load: 36 kN.

## Caractéristiques

- Weight : 800 g
- Materials : Aluminium, acier inoxydable, polyamide
- Certifications : CE EN 567, CE EN 12278 partielle*, NFPA 2500 Pulley General Use, NFPA 2500 Rope Grab Technical Use, UKCA, XF 494: FZL-H-T 9.5/13, XF 494: FZL-Z-Q 9.5/13 * Passe les exigences de performances de la norme CE EN 12278
- Certification du système : ANSI Z359.4 Synthetic Rope Tackle Block (plus d'informations dans la notice technique)