

PETZL SPIN L2 PULLEY

https://www.securhit.com/en/pulleys-and-ascenders/675-972-poulie-petzl-spin-l2.html#/888-couleur_p001ca-jaune

High-performance PETZL SPIN L2 double pulley with swivel. With two sheaves mounted in parallel and an attachment point for complex hauling operations.



Description

When working at heights and in rescue situations, it's essential to simplify actions as much as possible. Safety is paramount for professionals. PETZL's SPIN L2 double pulley has been specially designed to facilitate the installation of hauling systems and zip-lines.

- Simple triple-action opening of the mobile flange
- The rope can be installed while the device remains connected to the anchor.
- A red light appears if the mobile flange is unlocked
- Special flange design to protect rope passage
- Large-diameter sheaves on sealed ball bearings (very high efficiency)
- Parallel-mounted sheaves and auxiliary attachment point for complex hauling operations
- A swivel that facilitates pulley steering under load (3 carabiners maximum), with an auxiliary attachment point for using ropes and webbing to simplify maneuvers

Rope diameter: between 7 and 13 mm.

Maximum working load: 8 kN (3 kN per strand).

Breaking load: 36 Kn.

Yield: 95%.

Caractéristiques

- Weight : 480 g
- Materials : Aluminium, acier inoxydable, polyamide
- Certifications : CE EN 12278, NFPA 2500 Pulley General Use, UIAA, UKCA, XF 494 : FZL-H-T9.5/13