

## PETZL SPIN S1 PULLEY

[https://www.securhit.com/en/pulleys-and-ascenders/676-974-poulie-petzl-spin-s1.html#/890-couleur\\_p002aa-jaune](https://www.securhit.com/en/pulleys-and-ascenders/676-974-poulie-petzl-spin-s1.html#/890-couleur_p002aa-jaune)

Simple, compact PETZL SPIN S1 pulley. High-performance equipment with swivel for easy installation of reeving, zip-line or load-diverting systems.



## Description

In certain situations (work at height and technical rescue), compact accessories are practical for special jobs. PETZL's SPIN S1 pulley is specially designed to make it as easy as possible to use for hauling systems, zip lines or load detour.

- Easy triple-action opening of the mobile flange
- The rope can be installed while maintaining the connection between the device and the anchor.
- A red warning light indicates that the mobile flange is not locked.
- Protected rope passage thanks to special flange design
- An intermediate-diameter sheave on sealed ball bearings (excellent performance)
- A swivel designed to facilitate handling: pulley guidance under load, compatibility with rope / webbing passage, guaranteed reversal of most carabiners complying with European standards.

Rope diameter between 7 and 11 mm.  
Sheave diameter: 25 mm.  
Maximum working load:  $2.5 \times 2 = 5$  kN.  
Breaking load: 23 kN.  
Yield: 91%.

## Caractéristiques

- Weight : 145 g



- Materials : Aluminium, acier inoxydable, polyamide
- Certifications : CE EN 12278, NFPA 2500 Pulley Technical Use, UKCA, UIAA