

PETZL SPIN S1 OPEN compact pulley | Securhit

<https://www.securhit.com/en/pulleys-and-ascenders/705-poulie-petzl-spin-s1-open.html>

Compact PETZL SPIN S1 OPEN pulley for installation of hauling systems, zip lines or load detour systems.



Description

A compact pulley with excellent performance and compatibility with a wide range of equipment? PETZL's SPIN S1 OPEN combines all these advantages for successful work at height and in technical rescue. It makes it easy to set up hauling systems, zip lines or load detour systems.

The triple-action opening of the mobile flange makes the pulley easy to handle, even when wearing gloves. A rope can be installed while maintaining the connection between the device and the anchor. If the flange is not locked, a red light appears. The passage of the rope is also protected by the well-thought-out design of the flanges.

PETZL's SPIN S1 OPEN pulley also ensures optimum performance thanks to the intermediate-diameter sheave on sealed ball bearings.

The openable swivel minimizes clutter and, with its large opening, offers compatibility with numerous products such as PAW mooring multipliers and tripods. The swivel also makes it easy to guide the pulley under load, and to use ropes and webbing for simplified manoeuvring (up to 2 carabiners).

Rope diameter: between 7 and 11 mm.
Sheave diameter: 25 mm.
Maximum working load: $2 \times 2.5 = 5$ kN.
Breaking load: 23 kN.
Yield: 91%.

Caractéristiques

- Weight : 160 g



- Materials : Aluminium, acier inoxydable, polyamide
- Certifications : CE EN 12278, NFPA 2500 Pulley Technical Use, UKCA, UIAA